

## Features:

- Shuts Off Gas When Triggered by a Significant Seismic Event, Greatly Reducing Fire Risk
- Milled Solid Aluminum Design for Strength and Durability
- Most State-of-the-Art Compact Design
- Manual Reset Available On Both Sides\*  
\*(Horizontal Valves)
- Complies With All City, State, & Lab Testing Requirements
- ASCE 25-16 Compliant



**AGV-125**  
Horizontal



**VAGV-125**  
Vertical



**VAGV-125-HF**  
Vertical (High Flow)



**NAGV-125**  
Ninety

Model #	Pipe Size	Max. Pressure	L-W-H	Wt. (lbs)	0.5" W.C. BTU/HR X 1000	1.0" W.C. BTU/HR X 1000	Equivalent Pipe Length (Ft.)	CV Value
AGV-125 Horizontal	1-1/4"	5 psi	4" x 2.3" x 4.6"	2	1889	2677	5	48.1
VAGV-125 Vertical	1-1/4"	10 psi	2.5" x 2" x 3.4"	1	440	650	75	12
VAGV-125-HF Vertical High Flow	1-1/4"	2 psi	4.2" x 3.3" x 5.2"	7	2200	3,100	4	56.5
NAGV-125 Ninety Degree	1-1/4"	10 psi	3.3" x 2" x 3.1"	1.5	694	947	16	16.6