

## Features:

- Shuts Off Gas When Triggered by a Significant Seismic Event, Greatly Reducing Fire Risk
- Milled Solid Aluminum Design for Strength and Durability
- Most State-of-the-Art Compact Design
- Manual Reset Available On Both Sides\*  
\*(Horizontal Valves)
- Complies With All City, State, & Lab Testing Requirements
- ASCE 25-16 Compliant



**AGV-150**  
Horizontal



**VAGV-150**  
Vertical



**VAGV-150-HP**  
Vertical (High Pressure)



**AGV-150-HP**  
Horiz (High Pressure)

| Model #               | Pipe Size | Max. Pressure | L-W-H              | Wt. (lbs) | 0.5" W.C. BTU/HR X 1000 | 1.0" W.C. BTU/HR X 1000 | Equivalent Pipe Length (Ft.) | CV Value |
|-----------------------|-----------|---------------|--------------------|-----------|-------------------------|-------------------------|------------------------------|----------|
| AGV-150 Horizontal    | 1-1/2"    | 5 psi         | 6" x 3" x 5.5"     | 6         | 4079                    | 4079                    | 5                            | 76.3     |
| AGV-150-HP Horizontal | 1-1/2"    | 60 psi        | 6" x 3" x 5.5"     | 6         | 4079                    | 4,079                   | 5                            | 76.3     |
| VAGV-150 Vertical     | 1-1/2"    | 2 psi         | 4.2" x 3.3" x 5.2" | 7         | 2400                    | 3,700                   | 6                            | 68.8     |
| VAGV-150-HP Vertical  | 1-1/2"    | 60 psi        | 4.2" x 3.3" x 5.2" | 7         | 2400                    | 3,700                   | 6                            | 68.8     |